



KDC[®]380

1D & 2D Wireless
Barcode Scanner and Data Collector



Optimized Workflow with Integrated Keypad

This wireless scanner is the culmination of decades of engineering and human-centered design experience focused on maximizing efficiency and minimizing costs of auto-identification in any industry.



100 Village Blvd, Suite 300, Princeton, NJ 08540 USA
T: +1-609-256-4700
info@koamtac.com www.koamtac.com

© 2024 KOAMTAC, Inc.
KDC380 - 20240826

KDC380

1D & 2D Wireless
Barcode Scanner and Data Collector



Designed

A barcode and data collector that is small enough to fit in your pocket and light enough to wear on a lanyard around your neck for a full day without strain. The 1" OLED display and 19-key keypad make interacting with your device easier than ever; no need to decode flashing colored lights to determine if your data was collected - you can view it right on the screen!

Versatile

The KDC380 comes in 1D CCD, 1D Laser, and 2D Imager models, capable of reading all major symbologies. Additionally, 2D models are available in three read ranges: standard (KDC380C), medium (KDC380MR), and extended (KDC380ER), offering businesses flexibility for various scanning distances. With 8MB of on-board memory, it stores over 400,000 barcodes and supports basic applications directly on the device.

Rugged

The KDC380 is IP65 rated and has a 5' drop spec. This means the device is dust tight and water resistant; it's ideal for any environment.

Powered

KDC380 Charging Cradles offer reliable charging options for your scanners. Choose between a 1-slot charging cradle for individual scanner charging or a 4-slot charging cradle to charge multiple scanners simultaneously. Simply dock your KDC380 into the Charging Cradle, ensuring a snug fit with the bumper, and the pogo pins will efficiently charge your scanners. These cradles reduce clutter and help protect the device's USB port from potential damage.

Connected

The KDC380 features Bluetooth Low Energy 5.0 to enable faster and simpler connection methods for use with smart devices. Additional options include Wi-Fi connectivity and NFC for data transfer.

Keyboard wedging and configuration features are included in the complementary SDK for Android, iOS, macOS, Windows, Xamarin, Cordova, React Native, Flutter, and Web. Additionally, receive technical support from top engineers and the development team to ensure ease of data collection in any situation.



Hardware Specifications

Physical Characteristics

Size: 1.69" x 3.7" x 0.94" (43 mm x 94 mm x 24 mm)

Weight: 3.0 oz (85 g)

Electrical Characteristics

Battery: Lithium-Ion (3.7V DC, 1100 mAh) hard-pack

Charging: USB, Charging Cradle

Performance

Functionality

Memory Flash: 8MB User Data

Can store more than 400,000 barcodes (EAN-13)

Wedging & Synchronization

Store to a file or transfer to an application

Keyboard wedge function

Add-on prefixes and suffixes

Barcode option selection

Application Generation

SDK for Android, Xamarin, Cordova, React Native, Flutter, and Web

Database Lookup and Inventory Management features

Regulatory Conformance

R&TTE, FCC, KC, J-MIC, VCCI, RoHS Compliance

Laser Safety: IEC60825/CDRH Class II

LED Safety: IEC62471:2006

OS Support

Android, iOS, macOS, Windows

Other Features

NFC (Optional)

ISO/IEC 14443 A/B, ISO/IEC 15693, FeliCa, MIFARE (1K/4K/Ultralight/UltralightC/DESFire)

WiFi (Optional)

Compliance: 2.4GHz IEEE 802.11b/g/n

Support: 802.11g/n OFDM with BPSK, QPSK, 16-QAM, 64-QAM and 802.11b with BPSK, QPSK, CCK

Special Features

NFC Pairing

Social Distance Solution

Interfaces

Bluetooth Low Energy 5.0: HID (Android/iOS/Windows),

SPP (Optional Secure Mode)

USB: Flash Memory (Windows), USB HID, USB Serial (Android with OTG cable / Windows)

User Environment

IP Rating: IP65

Drop Spec: 5 feet (1.5m)

Operating: -4°F to 122°F (-20°C to 50°C)

Storage: -4°F to 140°F (-20°C to 60°C)

Humidity: 5% to 95% (non-condensing)

Scan Engine Specs (20mil Code39)

L - Laser: 1.40" to 52.00" (35 mm to 1320 mm)

D - CCD: 1.97" to 18.11" (50 mm to 460 mm)

C - Imager: 1.73" to 31.5" (44 mm to 800 mm)

MR - Imager: 3.3" to 59.0" (85 mm to 1500 mm)

ER - Imager: 3.4" to 104.1" (88 mm to 2848 mm)

Symbologies

Laser/CCD(1D): EAN-13, EAN-8, UPC-A, UPC-E, Code 39, ITF14, Code 128, Interleaved 2 of 5, Codabar, GS1-128, Code 93, Code 35, Bookland EAN-13, EAN-13/8 incl. add on, UPC-A/E incl. add on, GS1 Omni, GS1 Limited, GS1 Expanded

Imager (1D): Codabar, Code 11, Code 32, Code 39, Code 93, Code 128, EAN-8, EAN-13, GS1 Composite, Interleaved 2 of 5, Matrix 2 of 5, MSI, Plessey, PosiCode, GS1 Omni, GS1 Limited, GS1 Expanded, Straight 2 of 5 Industrial, Straight 2 of 5 IATA, TCL39, Telepen, Tri-Optic, UPC-A, UPC-E0, UPC-E1

Imager (2D): Aztec Code, Aztec Runes, Codablock F, Code 49, Data Matrix, MaxiCode, MicroPDF417, PDF417, QR Code, Han Xin Code

Postal Codes: POSTNET, Planet Code, British Post, Canadian Post, Netherlands (KIX) Post, Australian Post, Japanese Post, Chinese Post, Korean Post

OCR Options: OCR-A, OCR-B, OCR US Currency, OCR MICR E13B, OCR Semi Font

Your KDC

Models

KDC380L, KDC380LN, KDC380LF, KDC380LN

KDC380D, KDC380DN, KDC380DF, KDC380DNF

KDC380C, KDC380CN, KDC380CF, KDC380CNF

KDC380MR(medium range), KDC380ER (extended range)

*L=1D Laser, D=1D CCD, C=2D Imager; N=NFC, F=WiFi

Compatible Accessories

1-Slot Charging Cradle

4-Slot Charging Cradle

KDC380 Protective Boot

KBLED50 Dongle

